

Eaton 5S UPS

550 - 1600VA



Affordable power protection for workstations and POS equipment

Performance

- The Eaton 5S UPS provides effective power protection, even in disturbed electrical environments. Voltage fluctuations are automatically corrected using an AVR device (booster/fader), without needing the batteries.
- The 5S not only provides a supply with battery backup to keep equipment operating during power cuts, but also provides effective protection against damaging surges.

Reliability

- The 5S protects networked equipment from “back door” power surges coming through Ethernet, internet or telephone lines.
- The 5S’s periodic automatic battery testing ensures early detection if a battery needs to be replaced.
- The easy-to-replace battery helps to extend the UPS service life.

Versatility

- The 5S can be installed vertically over or under a desk, or horizontally under a screen. Its compact, slimline form factor even allows it to be easily integrated into environments with space constraints.
- The 5S features an HID-compliant USB port, for automatic integration with common operating systems (Windows/ Mac OS/Linux). The 5S is also compatible with Eaton UPS Companion power management software.
- All models come bundled with a USB cable for PC connection

Energy Saving

- Reduce wasted energy consumption from standby power drain of connected peripheral equipment with ECO Control function (850-1600VA models)

Ideal for protecting:

- Workstations
- Business Telephony
- Network devices
- Point-of-sale equipment



Powering Business Worldwide

Eaton 5S UPS

What's in the box:

- 5S UPS
- USB communication cable
- User Manual
- Safety Instructions
- LPG warranty statement



- 1 LED user interface on 550 & 700VA models
- 2 LCD interface on 850, 1200 & 1600VA models
- 3 Battery replacement panel
- 4 USB port
- 5 Data line protection
- 6 3 x Battery backup & surge protected AU outlets, 3 x surge protected AU only outlets
- 7 Circuit breaker reset button

Technical Specifications	550	700	850	1200	1600
Rating (VA/W)	550VA/330W	700VA/420W	850VA/510W	1200VA/750W	1600VA/1000W
Electrical Characteristics					
Technology	Line-Interactive (AVR with Booster + Fader)				
Input voltage range	175V-275V				
Output voltage	240 V				
Frequency	50-60 Hz autoselect				
Connections					
Number of AUS outlets	6				
Outlets with surge protection and battery backup / Outlets with surge protection only	3 / 3				
Batteries					
Typical backup times at 50 and 70% load*	10/6 min	9/5 min	10/6 min	14/8 min	11/8 min
Battery management	Automatic battery test, deep-discharge protection, cold-start capable, replaceable batteries				
Communication					
User Interface	LED		LCD		
Communication Port	HID-compliant USB port for automatic integration with most common operating systems (Windows Vista, 7 & 8, Linux, Mac OS X), cable supplied				
Data line protection	Tel/Fax/Modem/Internet and Ethernet				
Standards					
Safety & EMC	IEC/EN 62040-1, IEC/EN 62040 -2, CB Report, CE mark C-Tick				
Dimensions & Weight					
Dimensions H x W x D	250 x 87 x 260 mm			250 x 87 x 382 mm	
Weight	4.96kg	5.98kg	6.50kg	9.48kg	11.08kg
Customer Service & Support					
Warranty	2 years warranty including batteries				
Part Numbers					
5S	5S550AU	5S700AU	5S850AU	5S1200AU	5S1600AU

* Runtimes are shown at 0.7 power factor. Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.



Authorized Distributor & Qualified Service Partner:

PT. Deltasindo Raya Sejahtera

Tel (021) 2922 6688
 Fax (021) 2922 6699
 sales@deltasindo.com
 www.deltasindo.com